



Product series	SNOOT
Application areas	Accent Lighting
Pan/tilt range	Tilt
Mounting	Recessed
Lighting technology	LED
LED Luminous Flux Class	120LW/W
Light colour White	2700K, 3000K, 3000K - Efficient White, 3000K - Brilliant Colour, 3500K, 4000K
Cooling	Passive
Supply unit	Driver Separated
Luminaire colour	RAL 9005 jet black RAL 9006 white aluminium RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	100-240V, 50/60Hz
Lighting controls	On Request
Weight	Approx. 0.23kg
Test seal	      





 Cut out
 Diam. Ø55mm




Code composition/ Composizione del codice

Model	Power	Light flux	Cut-off size	Size	Beam Angle	CRI	Function
GMC614	5W	65LM/W	Ø55mm	Ø62*87mm	15°/24°/36°/50°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE CASAMBI


15°-3000K-CRI90



24°-3000K-CRI90




36°-3000K-CRI90



Accessories





SOLITE
SOFTENING
LENS



HONEY
COMB


Product series	SNOOT
Application areas	Accent Lighting
Pan/tilt range	Tilt
Mounting	Recessed
Lighting technology	LED
LED Luminous Flux Class	120LW/W
Light colour White	2700K, 3000K, 3000K - Efficient White, 3000K - Brilliant Colour,3500K, 4000K
Cooling	Passive
Supply unit	Driver Separated
Luminaire colour	RAL 9005 jet black RAL 9006 white aluminium RAL 9016 traffic white Special colours on request
Surface	Structure powder-coated
Nominal voltage	100-240V,50/60Hz
Lighting controls	On Request
Weight	Approx. 0.23kg
Test seal	




Code composition/ Composizione del codice

Model	Power	Light flux	Cut-off size	Size	Beam Angle	CRI	Function
GMC614	5W	65LM/W	Φ55mm	Φ80*87mm	15°/24°/36°/50°	90/98	ON/OFF DIM/DALI/0-10V ZIGBEE CASAMBI


15°-3000K-CRI90



24°-3000K-CRI90




36°-3000K-CRI90



Accessories



SOLITE
SOFTENING
LENS



HONEY
COMB